

---

# python-gerritclient

*Release*

Jan 03, 2018



---

## Contents

---

<b>1</b>	<b>User Documentation</b>	<b>3</b>
1.1	Gerrit Command Line Utility . . . . .	3
1.1.1	Gerrit CLI Commands . . . . .	3



This is a CLI tool and Python API wrapper for [Gerrit Code Review](#).



### 1.1 Gerrit Command Line Utility

*python-gerritclient* CLI is a command line utility for managing Gerrit Code Review environment. It allows to perform several types of operations.

For help on a specific **gerrit** command or subcommand, enter:

```
$ gerrit COMMAND [SUBCOMMAND [SUBCOMMAND ...]] --help
```

All **gerrit** commands support several options:

```
Usage: gerrit [--version] [-v | -q] [--log-file LOG_FILE] [-h] [--debug]
```

#### optional arguments:

- version** Show program's version number and exit.
- v, --verbose** Increase verbosity of output. Can be repeated.
- q, --quiet** Suppress output except warnings and errors.
- log-file LOG\_FILE** Specify a file to log output. Disabled by default.
- h, --help** Show help message and exit.
- debug** Show tracebacks on errors.

#### 1.1.1 Gerrit CLI Commands

##### **gerrit account \* commands**

##### **account create**

Creates a new account in Gerrit Code Review.

```
gerrit account create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--file FILE]
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**--file** <FILE>  
File with metadata to be uploaded.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account disable

Sets the account state in Gerrit to inactive.

```
gerrit account disable account-identifier
```

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account email add

Registers a new email address for the user in Gerrit.



```
gerrit account email add
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -e EMAIL
  [--preferred]
  [--no-confirmation]
  account-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**-e <EMAIL>, --email <EMAIL>**  
Account email.

**--preferred**  
Set email address as preferred.

**--no-confirmation**  
Email address confirmation. Only Gerrit administrators are allowed to add email addresses without confirmation.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account email delete

Deletes an email address of an account in Gerrit.

```
gerrit account email delete -e EMAIL account-identifier
```

**-e <EMAIL>, --email <EMAIL>**  
Account email.

### **account-identifier**

Account identifier.

This command is provided by the python-gerritclient plugin.

### **account email set-preferred**

Sets an email address as preferred email address for an account.

```
gerrit account email set-preferred account-identifier email
```

### **account-identifier**

Account identifier.

### **email**

Account email.

This command is provided by the python-gerritclient plugin.

### **account enable**

Sets the account state in Gerrit to active.

```
gerrit account enable account-identifier
```

### **account-identifier**

Account identifier.

This command is provided by the python-gerritclient plugin.

### **account list**

Lists all accounts in Gerrit visible to the caller.

```
gerrit account list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  [--suggest]
  [-l LIMIT]
  [-S SKIP]
  [-a]
  [--all-emails]
  query
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to '\_account\_id'. Wrong values are ignored.

**--suggest**  
Get account suggestions.

**-l** <LIMIT>, **--limit** <LIMIT>  
Limit the number of accounts to be included in the results.

**-S** <SKIP>, **--skip** <SKIP>  
Skip the given number of accounts from the beginning of the list.

**-a**, **--all**  
Includes full name, preferred email, username and avatars for each account.

**--all-emails**  
Includes all registered emails.

**query**  
Query string.

This command is provided by the python-gerritclient plugin.

## account membership list

Lists all groups that contain the specified user as a member.

```
gerrit account membership list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'group\_id'. Wrong values are ignored.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

### account name set

Sets the full name of an account in Gerrit Code Review.

```
gerrit account name set account-identifier name
```

**account-identifier**  
Account identifier.

**name**  
Account name.

This command is provided by the python-gerritclient plugin.

### account password delete

Deletes the HTTP password of an account in Gerrit.

```
gerrit account password delete account-identifier
```

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

### account password set

Sets/Generates the HTTP password of an account in Gerrit.

```
gerrit account password set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--generate | -p PASSWORD)
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**--generate**  
Generate HTTP password.

**-p** <PASSWORD>, **--password** <PASSWORD>  
HTTP password.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account show

Shows information about specific account in Gerrit.

```
gerrit account show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-a]
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**-a, --all**  
Show more details about account.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account ssh-key add

Adds an SSH key for a user in Gerrit.

```
gerrit account ssh-key add
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--ssh-key SSH_KEY | --file SSH_KEY_FILE)
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**--ssh-key** <SSH\_KEY>

The SSH public key.

**--file** SSH\_KEY\_FILE

File with the SSH public key.

**account-identifier**

Account identifier.

This command is provided by the python-gerritclient plugin.

**account ssh-key delete**

Deletes an SSH key of a user in Gerrit.

```
gerrit account ssh-key delete
  --sequence-id SEQUENCE_ID
  account-identifier
```

**--sequence-id** <SEQUENCE\_ID>

The sequence number of the SSH key.

**account-identifier**

Account identifier.

This command is provided by the python-gerritclient plugin.

**account ssh-key list**

Returns the SSH keys of an account in Gerrit.

```
gerrit account ssh-key list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'seq'. Wrong values are ignored.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

### account ssh-key show

Retrieves an SSH key of a user in Gerrit.

```
gerrit account ssh-key show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
-s SEQUENCE_ID
account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON



**--prefix** <PREFIX>  
add a prefix to all variable names

**-s** <SEQUENCE\_ID>, **--sequence-id** <SEQUENCE\_ID>  
The sequence number of the SSH key.

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account status show

Fetches the status of an account in Gerrit.

```
gerrit account status show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  account-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**account-identifier**  
Account identifier.

This command is provided by the python-gerritclient plugin.

## account username set

Sets the username of an account in Gerrit Code Review.

```
gerrit account username set account-identifier username
```

**account-identifier**

Account identifier.

**username**

Account username.

This command is provided by the python-gerritclient plugin.

**gerrit change \* commands**

**change abandon**

Abandons a change.

```
gerrit change abandon
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

**change assignee delete**

Deletes the assignee of a change.

```
gerrit change assignee delete
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change assignee history show

Retrieve a list of every user ever assigned to a change.

```
gerrit change assignee history show
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to '\_account\_id'. Wrong values are ignored.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change assignee set

Sets the assignee of a change.

```
gerrit change assignee set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -a ACCOUNT
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**-a** <ACCOUNT>, **--account** <ACCOUNT>  
The ID of one account that should be added as assignee.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

### change assignee show

Retrieves the account of the user assigned to a change.

```
gerrit change assignee show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

### change check

Performs consistency checks on the change.

Returns a ChangeInfo entity with the problems field.

```
gerrit change check
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change comment list

Lists the published comments of all revisions of the change.

```
gerrit change comment list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  [-t {drafts,robotcomments}]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'patch\_set'. Wrong values are ignored.

**-t** <TYPE>, **--type** <TYPE>  
The type of comments. Defaults to published.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change create

Creates a new change.

```
gerrit change create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  file
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

### **--noindent**

whether to disable indenting the JSON

### **--prefix** <PREFIX>

add a prefix to all variable names

### **file**

File with metadata of a new change.

This command is provided by the python-gerritclient plugin.

## change delete

Deletes a change.

```
gerrit change delete change-identifier
```

### **change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

## change draft publish

Publishes a draft change.

```
gerrit change draft publish change-identifier
```

### **change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

## change fix

Performs consistency checks on the change.

Additionally fixes any problems that can be fixed automatically. The returned field values reflect any fixes. Only the change owner, a project owner, or an administrator may fix changes.

```
gerrit change fix
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--delete-patchset]
  [--expect-merged-as]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table



**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**--delete-patchset**  
Delete patch sets from the database if they refer to missing commit options.

**--expect-merged-as**  
Check that the change is merged into the destination branch as this exact SHA-1. If not, insert a new patch set referring to this commit.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

### change included-in show

Retrieves the branches and tags in which a change is included.

```
gerrit change included-in show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

## change index

Adds or updates the change in the secondary index.

```
gerrit change index change-identifier
```

**change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

## change list

Queries changes visible to the caller.

```
gerrit change list
[-f {csv,json,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[-s SORT_COLUMN [SORT_COLUMN ...]]
[-l LIMIT]
[-S SKIP]
[-o OPTION [OPTION ...]]
query
[query ...]
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>

Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if **-max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'id'. Wrong values are ignored.

**-l** <LIMIT>, **--limit** <LIMIT>  
Limit the number of changes to be included in the results.

**-S** <SKIP>, **--skip** <SKIP>  
Skip the given number of changes from the beginning of the list.

**-o** <OPTION>, **--option** <OPTION>  
Fetch additional data about changes.

**query**  
Query string.

This command is provided by the python-gerritclient plugin.

## change move

Moves a change.

```
gerrit change move
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -b BRANCH
  [-m MESSAGE]
  change-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

- prefix** <PREFIX>  
add a prefix to all variable names
- b** <BRANCH>, **--branch** <BRANCH>  
Destination branch.
- m** <MESSAGE>, **--message** <MESSAGE>  
A message to be posted in this change's comments.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change rebase

Rebases a change.

```
gerrit change rebase
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-p PARENT]
  change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- prefix** <PREFIX>  
add a prefix to all variable names
- p** <PARENT>, **--parent** <PARENT>  
The new parent revision.
- change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change restore

Restores a change.

```
gerrit change restore
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change revert

Reverts a change.

```
gerrit change revert
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-m MESSAGE]
  change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**-m <MESSAGE>, --message <MESSAGE>**  
Message to be added as review comment when reverting the change.

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change show

Retrieves a change.

```
gerrit change show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-a]
  [-o OPTION [OPTION ...]]
  change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

- noindent**  
whether to disable indenting the JSON
- prefix** <PREFIX>  
add a prefix to all variable names
- a, --all**  
Retrieves a change with labels, detailed labels, detailed accounts, reviewer updates, and messages.
- o** <OPTION>, **--option** <OPTION>  
Fetch additional data about a change.
- change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change submit

Submits a change.

```
gerrit change submit
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--on-behalf-of ON_BEHALF_OF]
  [--notify {NONE,OWNER,OWNER_REVIEWERS,ALL}]
  change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- prefix** <PREFIX>  
add a prefix to all variable names
- on-behalf-of** <ON\_BEHALF\_OF>  
Submit the change on behalf of the given user.
- notify** <NOTIFY>  
Notify handling that defines to whom email notifications should be sent after the change is submitted.

### **change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

### **change topic delete**

Deletes the topic of a change.

```
gerrit change topic delete
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

### **change topic set**

Sets the topic of a change.

```
gerrit change topic set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
```



```

[--prefix PREFIX]
-t TOPIC
change-identifier

```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- prefix** <PREFIX>  
add a prefix to all variable names
- t** <TOPIC>, **--topic** <TOPIC>  
Topic of a change.
- change-identifier**  
Change identifier.

This command is provided by the python-gerritclient plugin.

## change topic show

Retrieves the topic of a change.

```

gerrit change topic show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier

```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix <PREFIX>**

add a prefix to all variable names

**change-identifier**

Change identifier.

This command is provided by the python-gerritclient plugin.

## gerrit group \* commands

### group create

Creates a new group in Gerrit Code Review.

```
gerrit group create
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
[--file FILE]
group-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**

the output format, defaults to table

**-c COLUMN, --column COLUMN**

specify the column(s) to include, can be repeated

**--max-width <integer>**

Maximum display width, <1 to disable. You can also use the `CLIFF_MAX_TERM_WIDTH` environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix <PREFIX>**

add a prefix to all variable names

**--file <FILE>**

File with metadata to be uploaded.

**group-identifier**

Group identifier.

This command is provided by the python-gerritclient plugin.

**group description delete**

Deletes the description of a specified Gerrit internal group.

```
gerrit group description delete group-identifier
```

**group-identifier**

Group identifier.

This command is provided by the python-gerritclient plugin.

**group description set**

Sets the description of a specified Gerrit internal group.

```
gerrit group description set group-identifier description
```

**group-identifier**

Group identifier.

**description**

Group description.

This command is provided by the python-gerritclient plugin.

**group exclude**

Deletes one or several included groups from a Gerrit internal group.

```
gerrit group exclude
  --group group-identifier
  [group-identifier ...]
  group-identifier
```

**--group group-identifier**

Group(s) identifier(s).

**group-identifier**

Group identifier.

This command is provided by the python-gerritclient plugin.

**group include**

Includes one or several groups into a Gerrit internal group.

```
gerrit group include
  --group group-identifier
  [group-identifier ...]
  group-identifier
```

**--group** group-identifier  
Group(s) identifier(s).

**group-identifier**  
Group identifier.

This command is provided by the python-gerritclient plugin.

## group list

Lists all groups in Gerrit Code Review.

```
gerrit group list
[-f {csv,json,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[-s SORT_COLUMN [SORT_COLUMN ...]]
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'group\_id'. Wrong values are ignored.

This command is provided by the python-gerritclient plugin.

## group member add

Adds a user or several users as member(s) to a Gerrit internal group.

```
gerrit group member add
--account account-identifier
```

```
[account-identifier ...]
group-identifier
```

**--account** account-identifier  
Account(s) identifier(s).

**group-identifier**  
Group identifier.

This command is provided by the python-gerritclient plugin.

### group member delete

Removes a user or several users from a Gerrit internal group.

```
gerrit group member delete
  --account account-identifier
  [account-identifier ...]
  group-identifier
```

**--account** account-identifier  
Account(s) identifier(s).

**group-identifier**  
Group identifier.

This command is provided by the python-gerritclient plugin.

### group member list

Lists all members of specific group in Gerrit Code Review.

```
gerrit group member list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  [-a]
  group-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>

when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN

Space separated list of keys for sorting the data. Defaults to ‘\_account\_id’. Wrong values are ignored.

**-a, --all**

Show members from included groups.

**group-identifier**

Group identifier.

This command is provided by the python-gerritclient plugin.

## group options set

Sets the options of a Gerrit internal group.

```
gerrit group options set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--visible | --no-visible)
  group-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>

Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**--visible**

Set group visible to all registered users.

**--no-visible**

Set group not visible to all registered users.

**group-identifier**

Group identifier.

This command is provided by the python-gerritclient plugin.

**group owner set**

Sets the owner group of a Gerrit internal group.

```
gerrit group owner set group-identifier owner
```

**group-identifier**

Group identifier.

**owner**

Group owner.

This command is provided by the python-gerritclient plugin.

**group rename**

Renames a Gerrit internal group.

```
gerrit group rename group-identifier new_name
```

**group-identifier**

Group identifier.

**new\_name**

New group name.

This command is provided by the python-gerritclient plugin.

**group show**

Shows information about specific group in Gerrit Code Review.

```
gerrit group show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-a]
  group-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**-a, --all**  
Show more details about group.

**group-identifier**  
Group identifier.

This command is provided by the python-gerritclient plugin.

## gerrit plugin \* commands

### plugin disable

Disables a plugin on the Gerrit server.

```
gerrit plugin disable plugin-identifier
```

**plugin-identifier**  
Plugin identifier.

This command is provided by the python-gerritclient plugin.

### plugin enable

Enables a plugin on the Gerrit server.

```
gerrit plugin enable plugin-identifier
```

**plugin-identifier**  
Plugin identifier.

This command is provided by the python-gerritclient plugin.

### plugin install

Installs a new plugin on the Gerrit server.

```
gerrit plugin install  
  [-f {json,shell,table,value,yaml}]  
  [-c COLUMN]
```



```

[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
(--url URL | --file FILE)
plugin-identifier

```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**--url** <URL>  
URL to the plugin jar.

**--file** <FILE>  
File path to the plugin jar.

**plugin-identifier**  
Plugin identifier.

This command is provided by the python-gerritclient plugin.

## plugin list

Lists all installed plugins in Gerrit Code Review.

```

gerrit plugin list
[-f {csv,json,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[-s SORT_COLUMN [SORT_COLUMN ...]]
[-a]

```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

- c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated
- max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- quote <QUOTE\_MODE>**  
when to include quotes, defaults to nonnumeric
- s SORT\_COLUMN, --sort-columns SORT\_COLUMN**  
Space separated list of keys for sorting the data. Defaults to 'id'. Wrong values are ignored.
- a, --all**  
Show all plugins (including disabled).

This command is provided by the python-gerritclient plugin.

## plugin reload

Reloads a plugin on the Gerrit server.

```
gerrit plugin reload
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  plugin-identifier
```

- f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table
- c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated
- max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**plugin-identifier**  
Plugin identifier.

This command is provided by the python-gerritclient plugin.

## plugin show

Shows information about specific plugin in Gerrit Code Review.

```
gerrit plugin show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
plugin-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**plugin-identifier**  
Plugin identifier.

This command is provided by the python-gerritclient plugin.

## gerrit project \* commands

### project branch create

Creates a new branch.

```
gerrit project branch create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -b BRANCH
  [-r REVISION]
  project-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**-b** <BRANCH>, **--branch** <BRANCH>  
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.

**-r** <REVISION>, **--revision** <REVISION>  
The base revision of the new branch. If not set, HEAD will be used as base revision.

**project-identifier**  
Project identifier.

This command is provided by the python-gerritclient plugin.

## project branch delete

Deletes one or more branches.

```
gerrit project branch delete -b BRANCH [BRANCH ...] name
```

**-b** <BRANCH>, **--branch** <BRANCH>  
The branches that should be deleted.

**name**  
Name of the project.

This command is provided by the python-gerritclient plugin.

## project branch list

Lists the branches of a project.

```
gerrit project branch list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  name
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote <QUOTE\_MODE>**  
when to include quotes, defaults to nonnumeric

**-s SORT\_COLUMN, --sort-columns SORT\_COLUMN**  
Space separated list of keys for sorting the data. Defaults to 'ref'. Wrong values are ignored.

**name**  
Name of the project.

This command is provided by the python-gerritclient plugin.

## project branch reflog show

Gets the reflog of a certain branch.

The caller must be project owner.

```
gerrit project branch reflog show
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
```

```
[--quote {all,minimal,none,nonnumeric}]
[-s SORT_COLUMN [SORT_COLUMN ...]]
-b BRANCH
name
```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric
- s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'old\_id'. Wrong values are ignored.
- b** <BRANCH>, **--branch** <BRANCH>  
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.
- name**  
Name of the project.

This command is provided by the python-gerritclient plugin.

## project branch show

Retrieves a branch of a project.

```
gerrit project branch show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
-b BRANCH
project-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**-b** <BRANCH>, **--branch** <BRANCH>  
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.

**project-identifier**  
Project identifier.

This command is provided by the python-gerritclient plugin.

## project child list

Lists the direct child projects of a project.

Child projects that are not visible to the calling user are ignored and are not resolved further.

```
gerrit project child list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  [-r]
  name
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--quote** <QUOTE\_MODE>

when to include quotes, defaults to nonnumeric

**-s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN

Space separated list of keys for sorting the data. Defaults to 'id'. Wrong values are ignored.

**-r, --recursively**

Resolve the child projects of a project recursively.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

## project create

Creates a new project in Gerrit Code Review.

```
gerrit project create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--file FILE]
  project-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>

Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**--file** <FILE>

File with metadata to be uploaded.

**project-identifier**

Project identifier.



This command is provided by the python-gerritclient plugin.

### project delete

Deletes specified project from Gerrit Code Review.

Note, 'deleteproject' plugin must be installed.

```
gerrit project delete [-f] [--preserve-git-repository] name
```

**-f, --force**

Delete project even if it has open changes.

**--preserve-git-repository**

Do not delete git repository directory.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project description set

Retrieves the description of a project.

```
gerrit project description set [-d DESCRIPTION] [-m MESSAGE] name
```

**-d <DESCRIPTION>, --description <DESCRIPTION>**

The project description. The project description will be deleted if not set.

**-m <MESSAGE>, --message <MESSAGE>**

Message that should be used to commit the change of the project description in the project.config file to the refs/meta/config branch.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project description show

Retrieves the description of a project.

```
gerrit project description show name
```

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project gc-run

Runs the Git garbage collection for the repository of a project.

In case of asynchronous execution the `--show-progress` option is ignored.

```
gerrit project gc-run [--show-progress] [--aggressive] name
```

**--show-progress**

Show progress information.

**--aggressive**

Do aggressive garbage collection.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project head set

Sets HEAD for a project.

```
gerrit project head set -b BRANCH name
```

**-b <BRANCH>, --branch <BRANCH>**

The name of the branch to which HEAD should point.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project head show

Retrieves for a project the name of the branch to which HEAD points.

```
gerrit project head show name
```

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

### project list

Lists all projects accessible by the caller.

```
gerrit project list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
  [-a]
  [-d]
  [-b BRANCHES [BRANCHES ...]]
  [-l LIMIT]
```

```
[ -S SKIP ]
[ --type {code,permissions,all} ]
[ -p PREFIX | -m MATCH | -r REGEX ]
```

- f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table
- c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated
- max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.
- fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable
- print-empty**  
Print empty table if there is no data to show.
- noindent**  
whether to disable indenting the JSON
- quote** <QUOTE\_MODE>  
when to include quotes, defaults to nonnumeric
- s** SORT\_COLUMN, **--sort-columns** SORT\_COLUMN  
Space separated list of keys for sorting the data. Defaults to 'name'. Wrong values are ignored.
- a**, **--all**  
Include hidden projects in the results.
- d**, **--description**  
Include project description in the results.
- b** <BRANCHES>, **--branches** <BRANCHES>  
Limit the results to the projects having the specified branches and include the sha1 of the branches in the results.
- l** <LIMIT>, **--limit** <LIMIT>  
Limit the number of projects to be included in the results.
- S** <SKIP>, **--skip** <SKIP>  
Skip the given number of projects from the beginning of the list.
- type** <TYPE>  
Display only projects of the specified type.
- p** <PREFIX>, **--prefix** <PREFIX>  
Limit the results to those projects that start with the specified prefix.
- m** <MATCH>, **--match** <MATCH>  
Limit the results to those projects that match the specified substring.
- r** <REGEX>, **--regex** <REGEX>  
Limit the results to those projects that match the specified regex.

This command is provided by the python-gerritclient plugin.

## project parent set

Sets the parent project for a project.

```
gerrit project parent set -p PARENT [-m MESSAGE] name
```

**-p** <PARENT>, **--parent** <PARENT>

The name of the parent project.

**-m** <MESSAGE>, **--message** <MESSAGE>

Message that should be used to commit the change of the project parent in the project.config file to the refs/meta/config branch.

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

## project parent show

Retrieves the name of a project's parent project.

```
gerrit project parent show name
```

**name**

Name of the project.

This command is provided by the python-gerritclient plugin.

## project repo-statistics show

Return statistics for the repository of a project.

```
gerrit project repo-statistics show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  project-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>

Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**project-identifier**

Project identifier.

This command is provided by the python-gerritclient plugin.

**project show**

Shows information about specific project in Gerrit Code Review.

```
gerrit project show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  project-identifier
```

**-f** <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

**-c** COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

**--max-width** <integer>

Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**

Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**

Print empty table if there is no data to show.

**--noindent**

whether to disable indenting the JSON

**--prefix** <PREFIX>

add a prefix to all variable names

**project-identifier**

Project identifier.

This command is provided by the python-gerritclient plugin.

## gerrit server \* commands

### server cache flush

Flushes a cache.

```
gerrit server cache flush (-a | -n NAME [NAME ...])
```

**-a, --all**

All available caches.

**-n <NAME>, --name <NAME>**

Caches names.

This command is provided by the python-gerritclient plugin.

### server cache list

Show the cache names as a list.

```
gerrit server cache list
[-f {csv,json,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[-s SORT_COLUMN [SORT_COLUMN ...]]
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote <QUOTE\_MODE>**  
when to include quotes, defaults to nonnumeric

**-s SORT\_COLUMN, --sort-columns SORT\_COLUMN**  
Space separated list of keys for sorting the data. Defaults to 'name'. Wrong values are ignored.

This command is provided by the python-gerritclient plugin.

## server cache show

Retrieves information about a cache.

```
gerrit server cache show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  name
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**name**  
Cache name.

This command is provided by the python-gerritclient plugin.

## server capabilities download

Downloads a list of the capabilities available in the system.

```
gerrit server capabilities download [-f {json,yaml}] [-d DIRECTORY]
```

**-f <FORMAT>, --format <FORMAT>**  
Format of serialized capabilities configuration.

**-d <DIRECTORY>, --directory <DIRECTORY>**  
Destination directory. Defaults to the current directory.

This command is provided by the python-gerritclient plugin.

## server configuration download

Downloads the information about the Gerrit server configuration.

```
gerrit server configuration download [-f {json,yaml}] [-d DIRECTORY]
```

**-f** <FORMAT>, **--format** <FORMAT>  
Format of serialized configuration configuration.

**-d** <DIRECTORY>, **--directory** <DIRECTORY>  
Destination directory. Defaults to the current directory.

This command is provided by the python-gerritclient plugin.

## server state show

Retrieves a summary of the current server state.

```
gerrit server state show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--jvm]
  [--gc]
```

**-f** <FORMATTER>, **--format** <FORMATTER>  
the output format, defaults to table

**-c** COLUMN, **--column** COLUMN  
specify the column(s) to include, can be repeated

**--max-width** <integer>  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix** <PREFIX>  
add a prefix to all variable names

**--jvm**  
Includes a JVM summary.

**--gc**  
Requests a Java garbage collection before computing the information about the Java memory heap.

This command is provided by the python-gerritclient plugin.



## server task delete

Kills a task from the background work queue that the Gerrit daemon is currently performing, or will perform in the near future.

```
gerrit server task delete task-identifier
```

### task-identifier

The ID of the task (hex string).

This command is provided by the python-gerritclient plugin.

## server task list

Lists the tasks from the background work queues that the Gerrit daemons is currently performing, or will perform in the near future.

```
gerrit server task list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [-s SORT_COLUMN [SORT_COLUMN ...]]
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if --max-width greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--quote <QUOTE\_MODE>**  
when to include quotes, defaults to nonnumeric

**-s SORT\_COLUMN, --sort-columns SORT\_COLUMN**  
Space separated list of keys for sorting the data. Defaults to 'id'. Wrong values are ignored.

This command is provided by the python-gerritclient plugin.

## server task show

Retrieves a task from the background work queue that the Gerrit daemon is currently performing, or will perform in the near future.

```
gerrit server task show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  task-identifier
```

**-f <FORMATTER>, --format <FORMATTER>**  
the output format, defaults to table

**-c COLUMN, --column COLUMN**  
specify the column(s) to include, can be repeated

**--max-width <integer>**  
Maximum display width, <1 to disable. You can also use the CLIFF\_MAX\_TERM\_WIDTH environment variable, but the parameter takes precedence.

**--fit-width**  
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF\_FIT\_WIDTH=1 to always enable

**--print-empty**  
Print empty table if there is no data to show.

**--noindent**  
whether to disable indenting the JSON

**--prefix <PREFIX>**  
add a prefix to all variable names

**task-identifier**  
The ID of the task (hex string).

This command is provided by the python-gerritclient plugin.

## server version

Returns the version of the Gerrit server.

```
gerrit server version
```

This command is provided by the python-gerritclient plugin.

## Symbols

- account account-identifier
  - gerrit-group-member-add command line option, 33
  - gerrit-group-member-delete command line option, 33
- aggressive
  - gerrit-project-gc-run command line option, 46
- all-emails
  - gerrit-account-list command line option, 7
- delete-patchset
  - gerrit-change-fix command line option, 21
- expect-merged-as
  - gerrit-change-fix command line option, 21
- file SSH\_KEY\_FILE
  - gerrit-account-ssh-key-add command line option, 11
- file <FILE>
  - gerrit-account-create command line option, 4
  - gerrit-group-create command line option, 30
  - gerrit-plugin-install command line option, 37
  - gerrit-project-create command line option, 44
- fit-width
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-list command line option, 7
  - gerrit-account-membership-list command line option, 8
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 10
  - gerrit-account-ssh-key-add command line option, 10
  - gerrit-account-ssh-key-list command line option, 12
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-history-show command line option, 16
  - gerrit-change-assignee-set command line option, 16
  - gerrit-change-assignee-show command line option, 17
  - gerrit-change-check command line option, 18
  - gerrit-change-comment-list command line option, 19
  - gerrit-change-create command line option, 19
  - gerrit-change-fix command line option, 21
  - gerrit-change-included-in-show command line option, 21
  - gerrit-change-list command line option, 22
  - gerrit-change-move command line option, 23
  - gerrit-change-rebase command line option, 24
  - gerrit-change-restore command line option, 25
  - gerrit-change-revert command line option, 26
  - gerrit-change-show command line option, 26
  - gerrit-change-submit command line option, 27
  - gerrit-change-topic-delete command line option, 28
  - gerrit-change-topic-set command line option, 29
  - gerrit-change-topic-show command line option, 29
  - gerrit-group-create command line option, 30
  - gerrit-group-list command line option, 32
  - gerrit-group-member-list command line option, 33
  - gerrit-group-options-set command line option, 34
  - gerrit-group-show command line option, 36
  - gerrit-plugin-install command line option, 37
  - gerrit-plugin-list command line option, 38
  - gerrit-plugin-reload command line option, 38
  - gerrit-plugin-show command line option, 39
  - gerrit-project-branch-create command line option, 40
  - gerrit-project-branch-list command line option, 41
  - gerrit-project-branch-reflog-show command line option, 42
  - gerrit-project-branch-show command line option, 43
  - gerrit-project-child-list command line option, 43
  - gerrit-project-create command line option, 44
  - gerrit-project-list command line option, 47
  - gerrit-project-repo-statistics-show command line option, 48
  - gerrit-project-show command line option, 49
  - gerrit-server-cache-list command line option, 50

- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-list command line option, 53
- gerrit-server-task-show command line option, 54
- gc
  - gerrit-server-state-show command line option, 52
- generate
  - gerrit-account-password-set command line option, 9
- group group-identifier
  - gerrit-group-exclude command line option, 31
  - gerrit-group-include command line option, 32
- jvm
  - gerrit-server-state-show command line option, 52
- max-width <integer>
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-list command line option, 6
  - gerrit-account-membership-list command line option, 7
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 10
  - gerrit-account-ssh-key-add command line option, 10
  - gerrit-account-ssh-key-list command line option, 11
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-history-show command line option, 15
  - gerrit-change-assignee-set command line option, 16
  - gerrit-change-assignee-show command line option, 17
  - gerrit-change-check command line option, 18
  - gerrit-change-comment-list command line option, 19
  - gerrit-change-create command line option, 19
  - gerrit-change-fix command line option, 21
  - gerrit-change-included-in-show command line option, 21
  - gerrit-change-list command line option, 22
  - gerrit-change-move command line option, 23
  - gerrit-change-rebase command line option, 24
  - gerrit-change-restore command line option, 25
  - gerrit-change-revert command line option, 26
  - gerrit-change-show command line option, 26
  - gerrit-change-submit command line option, 27
  - gerrit-change-topic-delete command line option, 28
  - gerrit-change-topic-set command line option, 29
  - gerrit-change-topic-show command line option, 29
  - gerrit-group-create command line option, 30
  - gerrit-group-list command line option, 32
  - gerrit-group-member-list command line option, 33
  - gerrit-group-options-set command line option, 34
  - gerrit-group-show command line option, 35
  - gerrit-plugin-install command line option, 37
  - gerrit-plugin-list command line option, 38
  - gerrit-plugin-reload command line option, 38
  - gerrit-plugin-show command line option, 39
  - gerrit-project-branch-create command line option, 40
  - gerrit-project-branch-list command line option, 41
  - gerrit-project-branch-reflog-show command line option, 42
  - gerrit-project-branch-show command line option, 42
  - gerrit-project-child-list command line option, 43
  - gerrit-project-create command line option, 44
  - gerrit-project-list command line option, 47
  - gerrit-project-repo-statistics-show command line option, 48
  - gerrit-project-show command line option, 49
  - gerrit-server-cache-list command line option, 50
  - gerrit-server-cache-show command line option, 51
  - gerrit-server-state-show command line option, 52
  - gerrit-server-task-list command line option, 53
  - gerrit-server-task-show command line option, 54
- no-confirmation
  - gerrit-account-email-add command line option, 5
- no-visible
  - gerrit-group-options-set command line option, 34
- noindent
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-list command line option, 7
  - gerrit-account-membership-list command line option, 8
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 10
  - gerrit-account-ssh-key-add command line option, 11
  - gerrit-account-ssh-key-list command line option, 12
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-history-show command line option, 16
  - gerrit-change-assignee-set command line option, 16
  - gerrit-change-assignee-show command line option, 17
  - gerrit-change-check command line option, 18
  - gerrit-change-comment-list command line option, 19
  - gerrit-change-create command line option, 19
  - gerrit-change-fix command line option, 21
  - gerrit-change-included-in-show command line option, 22
  - gerrit-change-list command line option, 23

- gerrit-change-move command line option, 23
- gerrit-change-rebase command line option, 24
- gerrit-change-restore command line option, 25
- gerrit-change-revert command line option, 26
- gerrit-change-show command line option, 26
- gerrit-change-submit command line option, 27
- gerrit-change-topic-delete command line option, 28
- gerrit-change-topic-set command line option, 29
- gerrit-change-topic-show command line option, 30
- gerrit-group-create command line option, 30
- gerrit-group-list command line option, 32
- gerrit-group-member-list command line option, 34
- gerrit-group-options-set command line option, 34
- gerrit-group-show command line option, 36
- gerrit-plugin-install command line option, 37
- gerrit-plugin-list command line option, 38
- gerrit-plugin-reload command line option, 38
- gerrit-plugin-show command line option, 39
- gerrit-project-branch-create command line option, 40
- gerrit-project-branch-list command line option, 41
- gerrit-project-branch-reflog-show command line option, 42
- gerrit-project-branch-show command line option, 43
- gerrit-project-child-list command line option, 43
- gerrit-project-create command line option, 44
- gerrit-project-list command line option, 47
- gerrit-project-repo-statistics-show command line option, 49
- gerrit-project-show command line option, 49
- gerrit-server-cache-list command line option, 50
- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-list command line option, 53
- gerrit-server-task-show command line option, 54
- notify <NOTIFY>
  - gerrit-change-submit command line option, 27
- on-behalf-of <ON\_BEHALF\_OF>
  - gerrit-change-submit command line option, 27
- preferred
  - gerrit-account-email-add command line option, 5
- prefix <PREFIX>
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 10
  - gerrit-account-ssh-key-add command line option, 11
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-set command line option, 16
- gerrit-change-assignee-show command line option, 17
- gerrit-change-check command line option, 18
- gerrit-change-create command line option, 20
- gerrit-change-fix command line option, 21
- gerrit-change-included-in-show command line option, 22
- gerrit-change-move command line option, 24
- gerrit-change-rebase command line option, 24
- gerrit-change-restore command line option, 25
- gerrit-change-revert command line option, 26
- gerrit-change-show command line option, 27
- gerrit-change-submit command line option, 27
- gerrit-change-topic-delete command line option, 28
- gerrit-change-topic-set command line option, 29
- gerrit-change-topic-show command line option, 30
- gerrit-group-create command line option, 30
- gerrit-group-options-set command line option, 34
- gerrit-group-show command line option, 36
- gerrit-plugin-install command line option, 37
- gerrit-plugin-reload command line option, 39
- gerrit-plugin-show command line option, 39
- gerrit-project-branch-create command line option, 40
- gerrit-project-branch-show command line option, 43
- gerrit-project-create command line option, 44
- gerrit-project-repo-statistics-show command line option, 49
- gerrit-project-show command line option, 49
- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-show command line option, 54
- preserve-git-repository
  - gerrit-project-delete command line option, 45
- print-empty
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-list command line option, 7
  - gerrit-account-membership-list command line option, 8
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 10
  - gerrit-account-ssh-key-add command line option, 10
  - gerrit-account-ssh-key-list command line option, 12
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-history-show command line option, 16
  - gerrit-change-assignee-set command line option, 16

- gerrit-change-assignee-show command line option, 17
- gerrit-change-check command line option, 18
- gerrit-change-comment-list command line option, 19
- gerrit-change-create command line option, 19
- gerrit-change-fix command line option, 21
- gerrit-change-included-in-show command line option, 21
- gerrit-change-list command line option, 22
- gerrit-change-move command line option, 23
- gerrit-change-rebase command line option, 24
- gerrit-change-restore command line option, 25
- gerrit-change-revert command line option, 26
- gerrit-change-show command line option, 26
- gerrit-change-submit command line option, 27
- gerrit-change-topic-delete command line option, 28
- gerrit-change-topic-set command line option, 29
- gerrit-change-topic-show command line option, 30
- gerrit-group-create command line option, 30
- gerrit-group-list command line option, 32
- gerrit-group-member-list command line option, 34
- gerrit-group-options-set command line option, 34
- gerrit-group-show command line option, 36
- gerrit-plugin-install command line option, 37
- gerrit-plugin-list command line option, 38
- gerrit-plugin-reload command line option, 38
- gerrit-plugin-show command line option, 39
- gerrit-project-branch-create command line option, 40
- gerrit-project-branch-list command line option, 41
- gerrit-project-branch-reflog-show command line option, 42
- gerrit-project-branch-show command line option, 43
- gerrit-project-child-list command line option, 43
- gerrit-project-create command line option, 44
- gerrit-project-list command line option, 47
- gerrit-project-repo-statistics-show command line option, 48
- gerrit-project-show command line option, 49
- gerrit-server-cache-list command line option, 50
- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-list command line option, 53
- gerrit-server-task-show command line option, 54
- quote <QUOTE\_MODE>
  - gerrit-account-list command line option, 7
  - gerrit-account-membership-list command line option, 8
  - gerrit-account-ssh-key-list command line option, 12
  - gerrit-change-assignee-history-show command line option, 16
  - gerrit-change-comment-list command line option, 19
  - gerrit-change-list command line option, 23
  - gerrit-group-list command line option, 32
  - gerrit-group-member-list command line option, 34
  - gerrit-plugin-list command line option, 38
  - gerrit-project-branch-list command line option, 41
  - gerrit-project-branch-reflog-show command line option, 42
  - gerrit-project-child-list command line option, 44
  - gerrit-project-list command line option, 47
  - gerrit-server-cache-list command line option, 50
  - gerrit-server-task-list command line option, 53
- sequence-id <SEQUENCE\_ID>
  - gerrit-account-ssh-key-delete command line option, 11
- show-progress
  - gerrit-project-gc-run command line option, 46
- ssh-key <SSH\_KEY>
  - gerrit-account-ssh-key-add command line option, 11
- suggest
  - gerrit-account-list command line option, 7
- type <TYPE>
  - gerrit-project-list command line option, 47
- url <URL>
  - gerrit-plugin-install command line option, 37
- visible
  - gerrit-group-options-set command line option, 34
- S <SKIP>, -skip <SKIP>
  - gerrit-account-list command line option, 7
  - gerrit-change-list command line option, 23
  - gerrit-project-list command line option, 47
- a <ACCOUNT>, -account <ACCOUNT>
  - gerrit-change-assignee-set command line option, 17
- a, -all
  - gerrit-account-list command line option, 7
  - gerrit-account-show command line option, 10
  - gerrit-change-show command line option, 27
  - gerrit-group-member-list command line option, 34
  - gerrit-group-show command line option, 36
  - gerrit-plugin-list command line option, 38
  - gerrit-project-list command line option, 47
  - gerrit-server-cache-flush command line option, 50
- b <BRANCHES>, -branches <BRANCHES>
  - gerrit-project-list command line option, 47
- b <BRANCH>, -branch <BRANCH>
  - gerrit-change-move command line option, 24
  - gerrit-project-branch-create command line option, 40
  - gerrit-project-branch-delete command line option, 40
  - gerrit-project-branch-reflog-show command line option, 42
  - gerrit-project-branch-show command line option, 43
  - gerrit-project-head-set command line option, 46
- c COLUMN, -column COLUMN
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5



- gerrit-account-list command line option, 6
- gerrit-account-membership-list command line option, 7
- gerrit-account-password-set command line option, 9
- gerrit-account-show command line option, 10
- gerrit-account-ssh-key-add command line option, 10
- gerrit-account-ssh-key-list command line option, 11
- gerrit-account-ssh-key-show command line option, 12
- gerrit-account-status-show command line option, 13
- gerrit-change-abandon command line option, 14
- gerrit-change-assignee-delete command line option, 15
- gerrit-change-assignee-history-show command line option, 15
- gerrit-change-assignee-set command line option, 16
- gerrit-change-assignee-show command line option, 17
- gerrit-change-check command line option, 18
- gerrit-change-comment-list command line option, 18
- gerrit-change-create command line option, 19
- gerrit-change-fix command line option, 20
- gerrit-change-included-in-show command line option, 21
- gerrit-change-list command line option, 22
- gerrit-change-move command line option, 23
- gerrit-change-rebase command line option, 24
- gerrit-change-restore command line option, 25
- gerrit-change-revert command line option, 26
- gerrit-change-show command line option, 26
- gerrit-change-submit command line option, 27
- gerrit-change-topic-delete command line option, 28
- gerrit-change-topic-set command line option, 29
- gerrit-change-topic-show command line option, 29
- gerrit-group-create command line option, 30
- gerrit-group-list command line option, 32
- gerrit-group-member-list command line option, 33
- gerrit-group-options-set command line option, 34
- gerrit-group-show command line option, 35
- gerrit-plugin-install command line option, 37
- gerrit-plugin-list command line option, 37
- gerrit-plugin-reload command line option, 38
- gerrit-plugin-show command line option, 39
- gerrit-project-branch-create command line option, 40
- gerrit-project-branch-list command line option, 41
- gerrit-project-branch-reflog-show command line option, 42
- gerrit-project-branch-show command line option, 42
- gerrit-project-child-list command line option, 43
- gerrit-project-create command line option, 44
- gerrit-project-list command line option, 47
- gerrit-project-repo-statistics-show command line option, 48
- gerrit-project-show command line option, 49
- gerrit-server-cache-list command line option, 50
- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-list command line option, 53
- gerrit-server-task-show command line option, 54
- d <DESCRIPTION>, --description <DESCRIPTION>
  - gerrit-project-description-set command line option, 45
- d <DIRECTORY>, --directory <DIRECTORY>
  - gerrit-server-capabilities-download command line option, 51
  - gerrit-server-configuration-download command line option, 52
- d, --description
  - gerrit-project-list command line option, 47
- e <EMAIL>, --email <EMAIL>
  - gerrit-account-email-add command line option, 5
  - gerrit-account-email-delete command line option, 5
- f <FORMATTER>, --format <FORMATTER>
  - gerrit-account-create command line option, 4
  - gerrit-account-email-add command line option, 5
  - gerrit-account-list command line option, 6
  - gerrit-account-membership-list command line option, 7
  - gerrit-account-password-set command line option, 9
  - gerrit-account-show command line option, 9
  - gerrit-account-ssh-key-add command line option, 10
  - gerrit-account-ssh-key-list command line option, 11
  - gerrit-account-ssh-key-show command line option, 12
  - gerrit-account-status-show command line option, 13
  - gerrit-change-abandon command line option, 14
  - gerrit-change-assignee-delete command line option, 15
  - gerrit-change-assignee-history-show command line option, 15
  - gerrit-change-assignee-set command line option, 16
  - gerrit-change-assignee-show command line option, 17
  - gerrit-change-check command line option, 18
  - gerrit-change-comment-list command line option, 18
  - gerrit-change-create command line option, 19
  - gerrit-change-fix command line option, 20
  - gerrit-change-included-in-show command line option, 21
  - gerrit-change-list command line option, 22
  - gerrit-change-move command line option, 23
  - gerrit-change-rebase command line option, 24
  - gerrit-change-restore command line option, 25
  - gerrit-change-revert command line option, 25
  - gerrit-change-show command line option, 26
  - gerrit-change-submit command line option, 27
  - gerrit-change-topic-delete command line option, 28

- gerrit-change-topic-set command line option, 29
- gerrit-change-topic-show command line option, 29
- gerrit-group-create command line option, 30
- gerrit-group-list command line option, 32
- gerrit-group-member-list command line option, 33
- gerrit-group-options-set command line option, 34
- gerrit-group-show command line option, 35
- gerrit-plugin-install command line option, 37
- gerrit-plugin-list command line option, 37
- gerrit-plugin-reload command line option, 38
- gerrit-plugin-show command line option, 39
- gerrit-project-branch-create command line option, 40
- gerrit-project-branch-list command line option, 41
- gerrit-project-branch-reflog-show command line option, 42
- gerrit-project-branch-show command line option, 42
- gerrit-project-child-list command line option, 43
- gerrit-project-create command line option, 44
- gerrit-project-list command line option, 47
- gerrit-project-repo-statistics-show command line option, 48
- gerrit-project-show command line option, 49
- gerrit-server-cache-list command line option, 50
- gerrit-server-cache-show command line option, 51
- gerrit-server-state-show command line option, 52
- gerrit-server-task-list command line option, 53
- gerrit-server-task-show command line option, 54
- f <FORMAT>, --format <FORMAT>
  - gerrit-server-capabilities-download command line option, 51
  - gerrit-server-configuration-download command line option, 52
- f, --force
  - gerrit-project-delete command line option, 45
- l <LIMIT>, --limit <LIMIT>
  - gerrit-account-list command line option, 7
  - gerrit-change-list command line option, 23
  - gerrit-project-list command line option, 47
- m <MATCH>, --match <MATCH>
  - gerrit-project-list command line option, 47
- m <MESSAGE>, --message <MESSAGE>
  - gerrit-change-move command line option, 24
  - gerrit-change-revert command line option, 26
  - gerrit-project-description-set command line option, 45
  - gerrit-project-parent-set command line option, 48
- n <NAME>, --name <NAME>
  - gerrit-server-cache-flush command line option, 50
- o <OPTION>, --option <OPTION>
  - gerrit-change-list command line option, 23
  - gerrit-change-show command line option, 27
- p <PARENT>, --parent <PARENT>
  - gerrit-change-rebase command line option, 24
  - gerrit-project-parent-set command line option, 48
- p <PASSWORD>, --password <PASSWORD>
  - gerrit-account-password-set command line option, 9
- p <PREFIX>, --prefix <PREFIX>
  - gerrit-project-list command line option, 47
- r <REGEX>, --regex <REGEX>
  - gerrit-project-list command line option, 47
- r <REVISION>, --revision <REVISION>
  - gerrit-project-branch-create command line option, 40
- r, --recursively
  - gerrit-project-child-list command line option, 44
- s SORT\_COLUMN, --sort-columns SORT\_COLUMN
  - gerrit-account-list command line option, 7
  - gerrit-account-membership-list command line option, 8
  - gerrit-account-ssh-key-list command line option, 12
  - gerrit-change-assignee-history-show command line option, 16
  - gerrit-change-comment-list command line option, 19
  - gerrit-change-list command line option, 23
  - gerrit-group-list command line option, 32
  - gerrit-group-member-list command line option, 34
  - gerrit-plugin-list command line option, 38
  - gerrit-project-branch-list command line option, 41
  - gerrit-project-branch-reflog-show command line option, 42
  - gerrit-project-child-list command line option, 44
  - gerrit-project-list command line option, 47
  - gerrit-server-cache-list command line option, 50
  - gerrit-server-task-list command line option, 53
- s <SEQUENCE\_ID>, --sequence-id <SEQUENCE\_ID>
  - gerrit-account-ssh-key-show command line option, 13
- t <TOPIC>, --topic <TOPIC>
  - gerrit-change-topic-set command line option, 29
- t <TYPE>, --type <TYPE>
  - gerrit-change-comment-list command line option, 19

## A

### account-identifier

- gerrit-account-create command line option, 4
- gerrit-account-disable command line option, 4
- gerrit-account-email-add command line option, 5
- gerrit-account-email-delete command line option, 5
- gerrit-account-email-set-preferred command line option, 6
- gerrit-account-enable command line option, 6
- gerrit-account-membership-list command line option, 8
- gerrit-account-name-set command line option, 8
- gerrit-account-password-delete command line option, 8
- gerrit-account-password-set command line option, 9



gerrit-account-show command line option, 10  
 gerrit-account-ssh-key-add command line option, 11  
 gerrit-account-ssh-key-delete command line option, 11  
 gerrit-account-ssh-key-list command line option, 12  
 gerrit-account-ssh-key-show command line option, 13  
 gerrit-account-status-show command line option, 13  
 gerrit-account-username-set command line option, 13

## C

### change-identifier

gerrit-change-abandon command line option, 14  
 gerrit-change-assignee-delete command line option, 15  
 gerrit-change-assignee-history-show command line option, 16  
 gerrit-change-assignee-set command line option, 17  
 gerrit-change-assignee-show command line option, 17  
 gerrit-change-check command line option, 18  
 gerrit-change-comment-list command line option, 19  
 gerrit-change-delete command line option, 20  
 gerrit-change-draft-publish command line option, 20  
 gerrit-change-fix command line option, 21  
 gerrit-change-included-in-show command line option, 22  
 gerrit-change-index command line option, 22  
 gerrit-change-move command line option, 24  
 gerrit-change-rebase command line option, 24  
 gerrit-change-restore command line option, 25  
 gerrit-change-revert command line option, 26  
 gerrit-change-show command line option, 27  
 gerrit-change-submit command line option, 28  
 gerrit-change-topic-delete command line option, 28  
 gerrit-change-topic-set command line option, 29  
 gerrit-change-topic-show command line option, 30

## D

### description

gerrit-group-description-set command line option, 31

## E

### email

gerrit-account-email-set-preferred command line option, 6

## F

### file

gerrit-change-create command line option, 20

## G

### gerrit-account-create command line option

–file <FILE>, 4  
 –fit-width, 4  
 –max-width <integer>, 4  
 –noindent, 4  
 –prefix <PREFIX>, 4  
 –print-empty, 4  
 –c COLUMN, –column COLUMN, 4  
 –f <FORMATTER>, –format <FORMATTER>, 4  
 account-identifier, 4

### gerrit-account-disable command line option

account-identifier, 4

### gerrit-account-email-add command line option

–fit-width, 5  
 –max-width <integer>, 5  
 –no-confirmation, 5  
 –noindent, 5  
 –preferred, 5  
 –prefix <PREFIX>, 5  
 –print-empty, 5  
 –c COLUMN, –column COLUMN, 5  
 –e <EMAIL>, –email <EMAIL>, 5  
 –f <FORMATTER>, –format <FORMATTER>, 5  
 account-identifier, 5

### gerrit-account-email-delete command line option

–e <EMAIL>, –email <EMAIL>, 5  
 account-identifier, 5

### gerrit-account-email-set-preferred command line option

account-identifier, 6  
 email, 6

### gerrit-account-enable command line option

account-identifier, 6

### gerrit-account-list command line option

–all-emails, 7  
 –fit-width, 7  
 –max-width <integer>, 6  
 –noindent, 7  
 –print-empty, 7  
 –quote <QUOTE\_MODE>, 7  
 –suggest, 7  
 –S <SKIP>, –skip <SKIP>, 7  
 –a, –all, 7  
 –c COLUMN, –column COLUMN, 6  
 –f <FORMATTER>, –format <FORMATTER>, 6  
 –l <LIMIT>, –limit <LIMIT>, 7  
 –s SORT\_COLUMN, –sort-columns SORT\_COLUMN, 7  
 query, 7

### gerrit-account-membership-list command line option

–fit-width, 8  
 –max-width <integer>, 7  
 –noindent, 8  
 –print-empty, 8

-quote <QUOTE\_MODE>, 8  
 -c COLUMN, -column COLUMN, 7  
 -f <FORMATTER>, -format <FORMATTER>, 7  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 8  
 account-identifier, 8  
 gerrit-account-name-set command line option  
 account-identifier, 8  
 name, 8  
 gerrit-account-password-delete command line option  
 account-identifier, 8  
 gerrit-account-password-set command line option  
 -fit-width, 9  
 -generate, 9  
 -max-width <integer>, 9  
 -noindent, 9  
 -prefix <PREFIX>, 9  
 -print-empty, 9  
 -c COLUMN, -column COLUMN, 9  
 -f <FORMATTER>, -format <FORMATTER>, 9  
 -p <PASSWORD>, -password <PASSWORD>, 9  
 account-identifier, 9  
 gerrit-account-show command line option  
 -fit-width, 10  
 -max-width <integer>, 10  
 -noindent, 10  
 -prefix <PREFIX>, 10  
 -print-empty, 10  
 -a, -all, 10  
 -c COLUMN, -column COLUMN, 10  
 -f <FORMATTER>, -format <FORMATTER>, 9  
 account-identifier, 10  
 gerrit-account-ssh-key-add command line option  
 -file SSH\_KEY\_FILE, 11  
 -fit-width, 10  
 -max-width <integer>, 10  
 -noindent, 11  
 -prefix <PREFIX>, 11  
 -print-empty, 10  
 -ssh-key <SSH\_KEY>, 11  
 -c COLUMN, -column COLUMN, 10  
 -f <FORMATTER>, -format <FORMATTER>, 10  
 account-identifier, 11  
 gerrit-account-ssh-key-delete command line option  
 -sequence-id <SEQUENCE\_ID>, 11  
 account-identifier, 11  
 gerrit-account-ssh-key-list command line option  
 -fit-width, 12  
 -max-width <integer>, 11  
 -noindent, 12  
 -print-empty, 12  
 -quote <QUOTE\_MODE>, 12  
 -c COLUMN, -column COLUMN, 11  
 -f <FORMATTER>, -format <FORMATTER>, 11  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 12  
 account-identifier, 12  
 gerrit-account-ssh-key-show command line option  
 -fit-width, 12  
 -max-width <integer>, 12  
 -noindent, 12  
 -prefix <PREFIX>, 12  
 -print-empty, 12  
 -c COLUMN, -column COLUMN, 12  
 -f <FORMATTER>, -format <FORMATTER>, 12  
 -s <SEQUENCE\_ID>, -sequence-id <SEQUENCE\_ID>, 13  
 account-identifier, 13  
 gerrit-account-status-show command line option  
 -fit-width, 13  
 -max-width <integer>, 13  
 -noindent, 13  
 -prefix <PREFIX>, 13  
 -print-empty, 13  
 -c COLUMN, -column COLUMN, 13  
 -f <FORMATTER>, -format <FORMATTER>, 13  
 account-identifier, 13  
 gerrit-account-username-set command line option  
 account-identifier, 13  
 username, 14  
 gerrit-change-abandon command line option  
 -fit-width, 14  
 -max-width <integer>, 14  
 -noindent, 14  
 -prefix <PREFIX>, 14  
 -print-empty, 14  
 -c COLUMN, -column COLUMN, 14  
 -f <FORMATTER>, -format <FORMATTER>, 14  
 change-identifier, 14  
 gerrit-change-assignee-delete command line option  
 -fit-width, 15  
 -max-width <integer>, 15  
 -noindent, 15  
 -prefix <PREFIX>, 15  
 -print-empty, 15  
 -c COLUMN, -column COLUMN, 15  
 -f <FORMATTER>, -format <FORMATTER>, 15  
 change-identifier, 15  
 gerrit-change-assignee-history-show command line option  
 -fit-width, 16  
 -max-width <integer>, 15  
 -noindent, 16  
 -print-empty, 16  
 -quote <QUOTE\_MODE>, 16  
 -c COLUMN, -column COLUMN, 15  
 -f <FORMATTER>, -format <FORMATTER>, 15

-s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 16  
 change-identifier, 16  
 gerrit-change-assignee-set command line option  
 -fit-width, 16  
 -max-width <integer>, 16  
 -noindent, 16  
 -prefix <PREFIX>, 16  
 -print-empty, 16  
 -a <ACCOUNT>, -account <ACCOUNT>, 17  
 -c COLUMN, -column COLUMN, 16  
 -f <FORMATTER>, -format <FORMATTER>, 16  
 change-identifier, 17  
 gerrit-change-assignee-show command line option  
 -fit-width, 17  
 -max-width <integer>, 17  
 -noindent, 17  
 -prefix <PREFIX>, 17  
 -print-empty, 17  
 -c COLUMN, -column COLUMN, 17  
 -f <FORMATTER>, -format <FORMATTER>, 17  
 change-identifier, 17  
 gerrit-change-check command line option  
 -fit-width, 18  
 -max-width <integer>, 18  
 -noindent, 18  
 -prefix <PREFIX>, 18  
 -print-empty, 18  
 -c COLUMN, -column COLUMN, 18  
 -f <FORMATTER>, -format <FORMATTER>, 18  
 change-identifier, 18  
 gerrit-change-comment-list command line option  
 -fit-width, 19  
 -max-width <integer>, 19  
 -noindent, 19  
 -print-empty, 19  
 -quote <QUOTE\_MODE>, 19  
 -c COLUMN, -column COLUMN, 18  
 -f <FORMATTER>, -format <FORMATTER>, 18  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 19  
 -t <TYPE>, -type <TYPE>, 19  
 change-identifier, 19  
 gerrit-change-create command line option  
 -fit-width, 19  
 -max-width <integer>, 19  
 -noindent, 19  
 -prefix <PREFIX>, 20  
 -print-empty, 19  
 -c COLUMN, -column COLUMN, 19  
 -f <FORMATTER>, -format <FORMATTER>, 19  
 file, 20  
 gerrit-change-delete command line option  
 change-identifier, 20  
 gerrit-change-draft-publish command line option  
 change-identifier, 20  
 gerrit-change-fix command line option  
 -delete-patchset, 21  
 -expect-merged-as, 21  
 -fit-width, 21  
 -max-width <integer>, 21  
 -noindent, 21  
 -prefix <PREFIX>, 21  
 -print-empty, 21  
 -c COLUMN, -column COLUMN, 20  
 -f <FORMATTER>, -format <FORMATTER>, 20  
 change-identifier, 21  
 gerrit-change-included-in-show command line option  
 -fit-width, 21  
 -max-width <integer>, 21  
 -noindent, 22  
 -prefix <PREFIX>, 22  
 -print-empty, 21  
 -c COLUMN, -column COLUMN, 21  
 -f <FORMATTER>, -format <FORMATTER>, 21  
 change-identifier, 22  
 gerrit-change-index command line option  
 change-identifier, 22  
 gerrit-change-list command line option  
 -fit-width, 22  
 -max-width <integer>, 22  
 -noindent, 23  
 -print-empty, 22  
 -quote <QUOTE\_MODE>, 23  
 -S <SKIP>, -skip <SKIP>, 23  
 -c COLUMN, -column COLUMN, 22  
 -f <FORMATTER>, -format <FORMATTER>, 22  
 -l <LIMIT>, -limit <LIMIT>, 23  
 -o <OPTION>, -option <OPTION>, 23  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 23  
 query, 23  
 gerrit-change-move command line option  
 -fit-width, 23  
 -max-width <integer>, 23  
 -noindent, 23  
 -prefix <PREFIX>, 24  
 -print-empty, 23  
 -b <BRANCH>, -branch <BRANCH>, 24  
 -c COLUMN, -column COLUMN, 23  
 -f <FORMATTER>, -format <FORMATTER>, 23  
 -m <MESSAGE>, -message <MESSAGE>, 24  
 change-identifier, 24  
 gerrit-change-rebase command line option  
 -fit-width, 24  
 -max-width <integer>, 24  
 -noindent, 24  
 -prefix <PREFIX>, 24

- print-empty, 24
  - c COLUMN, -column COLUMN, 24
  - f <FORMATTER>, -format <FORMATTER>, 24
  - p <PARENT>, -parent <PARENT>, 24
- change-identifier, 24
- gerrit-change-restore command line option
  - fit-width, 25
  - max-width <integer>, 25
  - noindent, 25
  - prefix <PREFIX>, 25
  - print-empty, 25
  - c COLUMN, -column COLUMN, 25
  - f <FORMATTER>, -format <FORMATTER>, 25
- change-identifier, 25
- gerrit-change-revert command line option
  - fit-width, 26
  - max-width <integer>, 26
  - noindent, 26
  - prefix <PREFIX>, 26
  - print-empty, 26
  - c COLUMN, -column COLUMN, 26
  - f <FORMATTER>, -format <FORMATTER>, 25
  - m <MESSAGE>, -message <MESSAGE>, 26
- change-identifier, 26
- gerrit-change-show command line option
  - fit-width, 26
  - max-width <integer>, 26
  - noindent, 26
  - prefix <PREFIX>, 27
  - print-empty, 26
  - a, -all, 27
  - c COLUMN, -column COLUMN, 26
  - f <FORMATTER>, -format <FORMATTER>, 26
  - o <OPTION>, -option <OPTION>, 27
- change-identifier, 27
- gerrit-change-submit command line option
  - fit-width, 27
  - max-width <integer>, 27
  - noindent, 27
  - notify <NOTIFY>, 27
  - on-behalf-of <ON\_BEHALF\_OF>, 27
  - prefix <PREFIX>, 27
  - print-empty, 27
  - c COLUMN, -column COLUMN, 27
  - f <FORMATTER>, -format <FORMATTER>, 27
- change-identifier, 28
- gerrit-change-topic-delete command line option
  - fit-width, 28
  - max-width <integer>, 28
  - noindent, 28
  - prefix <PREFIX>, 28
  - print-empty, 28
  - c COLUMN, -column COLUMN, 28
  - f <FORMATTER>, -format <FORMATTER>, 28
- change-identifier, 28
- gerrit-change-topic-set command line option
  - fit-width, 29
  - max-width <integer>, 29
  - noindent, 29
  - prefix <PREFIX>, 29
  - print-empty, 29
  - c COLUMN, -column COLUMN, 29
  - f <FORMATTER>, -format <FORMATTER>, 29
  - t <TOPIC>, -topic <TOPIC>, 29
- change-identifier, 29
- gerrit-change-topic-show command line option
  - fit-width, 29
  - max-width <integer>, 29
  - noindent, 30
  - prefix <PREFIX>, 30
  - print-empty, 30
  - c COLUMN, -column COLUMN, 29
  - f <FORMATTER>, -format <FORMATTER>, 29
- change-identifier, 30
- gerrit-group-create command line option
  - file <FILE>, 30
  - fit-width, 30
  - max-width <integer>, 30
  - noindent, 30
  - prefix <PREFIX>, 30
  - print-empty, 30
  - c COLUMN, -column COLUMN, 30
  - f <FORMATTER>, -format <FORMATTER>, 30
- group-identifier, 30
- gerrit-group-description-delete command line option
  - group-identifier, 31
- gerrit-group-description-set command line option
  - description, 31
  - group-identifier, 31
- gerrit-group-exclude command line option
  - group group-identifier, 31
  - group-identifier, 31
- gerrit-group-include command line option
  - group group-identifier, 32
  - group-identifier, 32
- gerrit-group-list command line option
  - fit-width, 32
  - max-width <integer>, 32
  - noindent, 32
  - print-empty, 32
  - quote <QUOTE\_MODE>, 32
  - c COLUMN, -column COLUMN, 32
  - f <FORMATTER>, -format <FORMATTER>, 32
  - s        SORT\_COLUMN,        -sort-columns  
          SORT\_COLUMN, 32
- gerrit-group-member-add command line option
  - account account-identifier, 33
  - group-identifier, 33

- gerrit-group-member-delete command line option
  - account account-identifier, 33
  - group-identifier, 33
- gerrit-group-member-list command line option
  - fit-width, 33
  - max-width <integer>, 33
  - noindent, 34
  - print-empty, 34
  - quote <QUOTE\_MODE>, 34
  - a, -all, 34
  - c COLUMN, -column COLUMN, 33
  - f <FORMATTER>, -format <FORMATTER>, 33
  - s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 34
  - group-identifier, 34
- gerrit-group-options-set command line option
  - fit-width, 34
  - max-width <integer>, 34
  - no-visible, 34
  - noindent, 34
  - prefix <PREFIX>, 34
  - print-empty, 34
  - visible, 34
  - c COLUMN, -column COLUMN, 34
  - f <FORMATTER>, -format <FORMATTER>, 34
  - group-identifier, 35
- gerrit-group-owner-set command line option
  - group-identifier, 35
  - owner, 35
- gerrit-group-rename command line option
  - group-identifier, 35
  - new\_name, 35
- gerrit-group-show command line option
  - fit-width, 36
  - max-width <integer>, 35
  - noindent, 36
  - prefix <PREFIX>, 36
  - print-empty, 36
  - a, -all, 36
  - c COLUMN, -column COLUMN, 35
  - f <FORMATTER>, -format <FORMATTER>, 35
  - group-identifier, 36
- gerrit-plugin-disable command line option
  - plugin-identifier, 36
- gerrit-plugin-enable command line option
  - plugin-identifier, 36
- gerrit-plugin-install command line option
  - file <FILE>, 37
  - fit-width, 37
  - max-width <integer>, 37
  - noindent, 37
  - prefix <PREFIX>, 37
  - print-empty, 37
  - url <URL>, 37
  - c COLUMN, -column COLUMN, 37
  - f <FORMATTER>, -format <FORMATTER>, 37
  - plugin-identifier, 37
- gerrit-plugin-list command line option
  - fit-width, 38
  - max-width <integer>, 38
  - noindent, 38
  - print-empty, 38
  - quote <QUOTE\_MODE>, 38
  - a, -all, 38
  - c COLUMN, -column COLUMN, 37
  - f <FORMATTER>, -format <FORMATTER>, 37
  - s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 38
- gerrit-plugin-reload command line option
  - fit-width, 38
  - max-width <integer>, 38
  - noindent, 38
  - prefix <PREFIX>, 39
  - print-empty, 38
  - c COLUMN, -column COLUMN, 38
  - f <FORMATTER>, -format <FORMATTER>, 38
  - plugin-identifier, 39
- gerrit-plugin-show command line option
  - fit-width, 39
  - max-width <integer>, 39
  - noindent, 39
  - prefix <PREFIX>, 39
  - print-empty, 39
  - c COLUMN, -column COLUMN, 39
  - f <FORMATTER>, -format <FORMATTER>, 39
  - plugin-identifier, 39
- gerrit-project-branch-create command line option
  - fit-width, 40
  - max-width <integer>, 40
  - noindent, 40
  - prefix <PREFIX>, 40
  - print-empty, 40
  - b <BRANCH>, -branch <BRANCH>, 40
  - c COLUMN, -column COLUMN, 40
  - f <FORMATTER>, -format <FORMATTER>, 40
  - r <REVISION>, -revision <REVISION>, 40
  - project-identifier, 40
- gerrit-project-branch-delete command line option
  - b <BRANCH>, -branch <BRANCH>, 40
  - name, 40
- gerrit-project-branch-list command line option
  - fit-width, 41
  - max-width <integer>, 41
  - noindent, 41
  - print-empty, 41
  - quote <QUOTE\_MODE>, 41
  - c COLUMN, -column COLUMN, 41
  - f <FORMATTER>, -format <FORMATTER>, 41

-s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 41  
 name, 41  
 gerrit-project-branch-reflog-show command line option  
 -fit-width, 42  
 -max-width <integer>, 42  
 -noindent, 42  
 -print-empty, 42  
 -quote <QUOTE\_MODE>, 42  
 -b <BRANCH>, -branch <BRANCH>, 42  
 -c COLUMN, -column COLUMN, 42  
 -f <FORMATTER>, -format <FORMATTER>, 42  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 42  
 name, 42  
 gerrit-project-branch-show command line option  
 -fit-width, 43  
 -max-width <integer>, 42  
 -noindent, 43  
 -prefix <PREFIX>, 43  
 -print-empty, 43  
 -b <BRANCH>, -branch <BRANCH>, 43  
 -c COLUMN, -column COLUMN, 42  
 -f <FORMATTER>, -format <FORMATTER>, 42  
 project-identifier, 43  
 gerrit-project-child-list command line option  
 -fit-width, 43  
 -max-width <integer>, 43  
 -noindent, 43  
 -print-empty, 43  
 -quote <QUOTE\_MODE>, 44  
 -c COLUMN, -column COLUMN, 43  
 -f <FORMATTER>, -format <FORMATTER>, 43  
 -r, -recursively, 44  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 44  
 name, 44  
 gerrit-project-create command line option  
 -file <FILE>, 44  
 -fit-width, 44  
 -max-width <integer>, 44  
 -noindent, 44  
 -prefix <PREFIX>, 44  
 -print-empty, 44  
 -c COLUMN, -column COLUMN, 44  
 -f <FORMATTER>, -format <FORMATTER>, 44  
 project-identifier, 44  
 gerrit-project-delete command line option  
 -preserve-git-repository, 45  
 -f, -force, 45  
 name, 45  
 gerrit-project-description-set command line option  
 -d <DESCRIPTION>, -description <DESCRIPTION>, 45  
 -m <MESSAGE>, -message <MESSAGE>, 45  
 name, 45  
 gerrit-project-description-show command line option  
 name, 45  
 gerrit-project-gc-run command line option  
 -aggressive, 46  
 -show-progress, 46  
 name, 46  
 gerrit-project-head-set command line option  
 -b <BRANCH>, -branch <BRANCH>, 46  
 name, 46  
 gerrit-project-head-show command line option  
 name, 46  
 gerrit-project-list command line option  
 -fit-width, 47  
 -max-width <integer>, 47  
 -noindent, 47  
 -print-empty, 47  
 -quote <QUOTE\_MODE>, 47  
 -type <TYPE>, 47  
 -S <SKIP>, -skip <SKIP>, 47  
 -a, -all, 47  
 -b <BRANCHES>, -branches <BRANCHES>, 47  
 -c COLUMN, -column COLUMN, 47  
 -d, -description, 47  
 -f <FORMATTER>, -format <FORMATTER>, 47  
 -l <LIMIT>, -limit <LIMIT>, 47  
 -m <MATCH>, -match <MATCH>, 47  
 -p <PREFIX>, -prefix <PREFIX>, 47  
 -r <REGEX>, -regex <REGEX>, 47  
 -s SORT\_COLUMN, -sort-columns SORT\_COLUMN, 47  
 gerrit-project-parent-set command line option  
 -m <MESSAGE>, -message <MESSAGE>, 48  
 -p <PARENT>, -parent <PARENT>, 48  
 name, 48  
 gerrit-project-parent-show command line option  
 name, 48  
 gerrit-project-repo-statistics-show command line option  
 -fit-width, 48  
 -max-width <integer>, 48  
 -noindent, 49  
 -prefix <PREFIX>, 49  
 -print-empty, 48  
 -c COLUMN, -column COLUMN, 48  
 -f <FORMATTER>, -format <FORMATTER>, 48  
 project-identifier, 49  
 gerrit-project-show command line option  
 -fit-width, 49  
 -max-width <integer>, 49  
 -noindent, 49  
 -prefix <PREFIX>, 49  
 -print-empty, 49  
 -c COLUMN, -column COLUMN, 49



-f <FORMATTER>, --format <FORMATTER>, 49  
 project-identifier, 49  
 gerrit-server-cache-flush command line option  
 -a, --all, 50  
 -n <NAME>, --name <NAME>, 50  
 gerrit-server-cache-list command line option  
 -fit-width, 50  
 -max-width <integer>, 50  
 -noindent, 50  
 -print-empty, 50  
 -quote <QUOTE\_MODE>, 50  
 -c COLUMN, --column COLUMN, 50  
 -f <FORMATTER>, --format <FORMATTER>, 50  
 -s SORT\_COLUMN, --sort-columns  
 SORT\_COLUMN, 50  
 gerrit-server-cache-show command line option  
 -fit-width, 51  
 -max-width <integer>, 51  
 -noindent, 51  
 -prefix <PREFIX>, 51  
 -print-empty, 51  
 -c COLUMN, --column COLUMN, 51  
 -f <FORMATTER>, --format <FORMATTER>, 51  
 name, 51  
 gerrit-server-capabilities-download command line option  
 -d <DIRECTORY>, --directory <DIRECTORY>, 51  
 -f <FORMAT>, --format <FORMAT>, 51  
 gerrit-server-configuration-download command line option  
 -d <DIRECTORY>, --directory <DIRECTORY>, 52  
 -f <FORMAT>, --format <FORMAT>, 52  
 gerrit-server-state-show command line option  
 -fit-width, 52  
 -gc, 52  
 -jvm, 52  
 -max-width <integer>, 52  
 -noindent, 52  
 -prefix <PREFIX>, 52  
 -print-empty, 52  
 -c COLUMN, --column COLUMN, 52  
 -f <FORMATTER>, --format <FORMATTER>, 52  
 gerrit-server-task-delete command line option  
 task-identifier, 53  
 gerrit-server-task-list command line option  
 -fit-width, 53  
 -max-width <integer>, 53  
 -noindent, 53  
 -print-empty, 53  
 -quote <QUOTE\_MODE>, 53  
 -c COLUMN, --column COLUMN, 53  
 -f <FORMATTER>, --format <FORMATTER>, 53  
 -s SORT\_COLUMN, --sort-columns  
 SORT\_COLUMN, 53  
 gerrit-server-task-show command line option

-fit-width, 54  
 -max-width <integer>, 54  
 -noindent, 54  
 -prefix <PREFIX>, 54  
 -print-empty, 54  
 -c COLUMN, --column COLUMN, 54  
 -f <FORMATTER>, --format <FORMATTER>, 54  
 task-identifier, 54  
 group-identifier  
 gerrit-group-create command line option, 30  
 gerrit-group-description-delete command line option, 31  
 gerrit-group-description-set command line option, 31  
 gerrit-group-exclude command line option, 31  
 gerrit-group-include command line option, 32  
 gerrit-group-member-add command line option, 33  
 gerrit-group-member-delete command line option, 33  
 gerrit-group-member-list command line option, 34  
 gerrit-group-options-set command line option, 35  
 gerrit-group-owner-set command line option, 35  
 gerrit-group-rename command line option, 35  
 gerrit-group-show command line option, 36

## N

### name

gerrit-account-name-set command line option, 8  
 gerrit-project-branch-delete command line option, 40  
 gerrit-project-branch-list command line option, 41  
 gerrit-project-branch-reflog-show command line option, 42  
 gerrit-project-child-list command line option, 44  
 gerrit-project-delete command line option, 45  
 gerrit-project-description-set command line option, 45  
 gerrit-project-description-show command line option, 45  
 gerrit-project-gc-run command line option, 46  
 gerrit-project-head-set command line option, 46  
 gerrit-project-head-show command line option, 46  
 gerrit-project-parent-set command line option, 48  
 gerrit-project-parent-show command line option, 48  
 gerrit-server-cache-show command line option, 51

### new\_name

gerrit-group-rename command line option, 35

## O

### owner

gerrit-group-owner-set command line option, 35

## P

plugin-identifier

- gerrit-plugin-disable command line option, [36](#)
- gerrit-plugin-enable command line option, [36](#)
- gerrit-plugin-install command line option, [37](#)
- gerrit-plugin-reload command line option, [39](#)
- gerrit-plugin-show command line option, [39](#)

project-identifier

- gerrit-project-branch-create command line option, [40](#)
- gerrit-project-branch-show command line option, [43](#)
- gerrit-project-create command line option, [44](#)
- gerrit-project-repo-statistics-show command line option, [49](#)
- gerrit-project-show command line option, [49](#)

## Q

query

- gerrit-account-list command line option, [7](#)
- gerrit-change-list command line option, [23](#)

## T

task-identifier

- gerrit-server-task-delete command line option, [53](#)
- gerrit-server-task-show command line option, [54](#)

## U

username

- gerrit-account-username-set command line option, [14](#)